

CaviBlaster 1222-E

Electric Motor 50 Hz or 60 Hz, 12 gpm & 2,200 psi

Specifications and Options

This electric version of the 1222-G is compact, lightweight yet provides a superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included

Feed Pump with Hose Assembly (15 feet), By-Pass Hose (15 feet), Zero-thrust balanced Gun, High Pressure Hose (50 feet)

Optional Accessories

Additional pressure hose available in 50 ft or 100 ft sections. (1/2" Diam.)
 Max. Pressure hose length recommended up to 300 ft (100 meters) total
 Four wheel configuration. Remote control pedal.



SKID Dimensions	
Length w/o handle	35" / 89 cm
Length w/ handle	45" / 114 cm
Width	26" / 66 cm
Height	29" / 74 cm
Weight	465 lbs / 211 kg

Pump System	
Pressure Pump	AR XWL 50.20 N
Pump Material / Type	Brass / Positive Displacement
Flow Rate	13 gpm / 50 lpm
Pressure	2,200 psi / 152 bar
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions	
Pallet 48" x 40" x 41"	512 lbs Gross Weight

Drive System	
Motor	Multi-Voltage Electric
Enclosure	TEFC
Frame	284T
Hertz	60 Hz
Voltage	230-460 V
Phase	3 Phase
Output HP/kW	20 hp / 16 kw
Speed RPM USA/Intl.	1,800 / 1,500 rpm
Starting System	Magnetic Start

Feed System	
Feed Pump	Johnson L2200
Pump Material	Thermoplastic, SS Shaft
Flow Rate	29 gpm/110 L/m @ 3.3 ft/1 m
Pump Power Supply	12V @ 7.5 Amp

Ideal For
Small to Mid Size Boat Hulls
Piers, Pilings & Seawalls
Running Gear & Out Drivers
Pools & Indoor Underwater Instalations



Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance
4 Wheels
Remote Foot Pedal

***PRICING AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE**